

General Specifications

- | | |
|-------------------|--|
| • Display | 7*17mm digits LCD display, with white LED backlight |
| • Capacities | 220g |
| • Pan size | Φ90mm |
| • Keyboard | 6 keys (Membrane keyboard) |
| • Housing | ABS plastic |
| • Max. Divisions | 2,200,000d |
| • Operating Temp. | +10°C~+30°C |
| • Power | Input :AC 100~240V, 50~60Hz; Output:DC 12V 2000mA |
| • Packing | Master carton packing, dimension 0.065m ³ |



- Standard stainless steel pan
- Electromagnetic force loadcell
- Die-cast aluminum bottom cover
- Internal and external calibration selectable
- Applications: 1. Basic weighing 2. Counting 3. Percentage weighing 4. Weighing units conversion
- Standard RS-232 interface can connect to computer and printer

Model Name	Capacity	Readability	Division	Pan Size	Approx. weight
DHB+-220	220g	0.0001g	2,200,000d	Φ 90mm	3.7kg
DHB+-I-220	220g	0.0001g	2,200,000d	Φ 90mm	3.7kg

Options



Print Formats

Receipt Format

G: 93.8162g
 G: 93.8162g
 U.W: 4.9376g/pcs
 PCS: 19.pcs
 G: 93.8162g
 PCT: 134.02%

Label Format

2019/03/25 09:00
 G: 93.8162g

2019/03/25 09:05
 G: 93.8162g
 U.W: 4.9376g/pcs
 PCS: 19.pcs

2019/03/25 09:10
 G: 93.8162g
 PCT: 134.02%

Dimensions(mm)

